



**APPLICATIONS**

- 💡 Office Lighting
- 💡 Food Grade Applications
- 💡 Damp Location Installation

**Shatterproof**

**FEATURES**

- 💡 Polycarbonate Shatter-Proof
- 💡 No UV or IR radiation
- 💡 Mercury free
- 💡 Easy and secure installation
- 💡 Operating Temperature :  
-35°C to 55°C
- 💡 39W Fluorescent T5 Equivalent
- 💡 50,000 hours lifespan
- 💡 Compatible with instant start  
and rapid start ballasts
- 💡 5-year Warranty



Model	MOL	Lumens Output	Beam Angle	Luminous Efficacy	Equivalent Wattage	Watts	Volts	Power Factor	CCT(K)	CRI
WLL-LEDT5 BC18/830/G2	36"	1700lm	330°	112 lm/W	39	18W	120-277V/ 347V	0.9	3000K	83+
WLL-LEDT5 BC18/840/G2	36"	1700lm	330°	112 lm/W	39	18W	120-277V/ 347V	0.9	4000K	83+
WLL-LEDT5 BC18/850/G2	36"	1700lm	330°	112 lm/W	39	18W	120-277V/ 347V	0.9	5000K	83+

📍 Unit 5-615 Denison St, Markham L3R 1B8  
 ☎️ 905-604-4666 📠 905-604-4966

✉️ info@renolighting.com  
 🌐 www.renolighting.com